SPM3200HS008S

Solartech Solar Pump

Performance

Water Head	52 - 19 m
Daily Water Flow	3 - 8 m³

Technical Data

Pump Specifications	24V 4000rpm
Pump Outlet Dia.	3/4"
Adapting Well Dia.	100 mm
Solar Pumping Inverter Model	PM200S
Inverter Power	200 W
Max. DC Input Voltage	60 V
Recommended MPP Voltage	> 30V
Inverter Ambient Temperature	-20 ~ 60 ℃
Pump Model	SPM3-0.5-0.2HS
Motor Power	200 W
Pump Enclosure Class	IP68
Ambient Water pH Range	6.5 - 8.0
Ambient Water Temperature	1 - 35 ℃



Dimension, Weight and Material

Inverter

W = 152 mm
H = 220 mm
D = 79 mm
W1 = 172 mm
H1 = 154 mm
D1 = 39 mm
d = 4.2 mm



Pump

A = 365 mm
B = 170 mm
C = 195 mm
ΦD = G3/4"
ΦE = 74 mm
Φmax = 75 mm



Solar Pump Net Weight	6.3 kg	Pump Screw Material	AISI 201
Solar Pump Gross Weight	7.9 kg	Pump Body Material	AISI 201
Solar Pump Volume	0.016 m³	Inverter Enclosure Material	Aluminium Alloy

Relevant Information

Warranty

Inverter	3 years
Pump	1 year

Standards

CE

EN 60335-1:2012+A11:2014
EN 60335-2-41:2003+A1:2004+A2:2010
EN 62109-1:2010
EN 62109-2:2011

Performance Curve

Solar Radiation: 6kWh/m²/day



V1.0 2202

*All specifications and information are provided with good intent, products may be subject to change without notice.